Appl. No. 10/827,088 Docket No. 9606

Reply dated September 10, 2009

Reply to Office Action mailed on June 11, 2009

Customer No. 27752

## LISTING OF CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Previously Presented) A disposable absorbent article comprising:
  - a) a liquid pervious topsheet;
  - b) a liquid impervious backsheet that is at least partially joined to the topsheet;
  - an absorbent core disposed at least partially between the topsheet and the backsheet; and
  - d) a wetness indicator printed onto a surface of said backsheet; the wetness
    indicator comprising a graphic that further comprises at least one hydrolyzable
    color composition and a varnish coating disposed adjacent to said
    hydrolyzable color composition; said graphic being invisible to the unaided
    eye;

wherein upon wetting, said hydrolyzable color composition undergoes a hydrolytic reaction resulting in said invisible graphic becoming visible to the unaided eye.

- 2. (Original) The article of claim 1 wherein the color composition comprises:
  - a) from about 1% to about 10%, by weight of the composition, of fluid dyestuffs;
     and
  - b) from about 10% to about 99%, by weight of the composition, of a solvent.
- (Original) The article of claim 2 wherein the solvent is a non-aqueous solvent selected from the group consisting of alcohols, acetates, and combinations thereof.
- (Original) The article of claim 3 wherein said alcohol is selected from the group consisting of isopropyl alcohol, n-propyl alcohol, ethanol, methanol, and combinations thereof

Appl. No. 10/827,088

Docket No. 9606

Reply dated September 10, 2009

Reply to Office Action mailed on June 11, 2009

Customer No. 27752

 (Original) The article of claim 3 wherein said acetate is selected from the group consisting of isopryl acetate, n-propyl acetate, and combinations thereof.

 (Original) The article of claim 1 wherein said varnish coating comprises materials selected from the group consisting of acrylic copolymers, shellac-based acrylic resins, polyamides, and combinations thereof.

 (Original) The article of claim 1 wherein said wetness indicator is printed on an inner surface.

 (Previously Presented) The article of claim 1 wherein said varnish coating is disposed over said hydrolysable color composition.

 (Previously Presented) The article of claim 1 wherein said varnish coating is disposed beneath said hydrolyzable color composition.

 (Previously Presented) The article of claim 8 wherein said varnish coating is further disposed beneath said hydrolyzable color composition.

11. (Previously Presented) A method of printing a wetness indicator onto an absorbent article:

 a) providing an absorbent article wherein said article comprises a topsheet, a backsheet and an absorbent core:

b) disposing between said backsheet and said absorbent core via printing a wetness indicator onto a surface of said backsheet; the wetness indicator comprising a graphic that further comprises at least one hydrolyzable color composition and a varnish coating disposed adjacent to said hydrolyzable color composition; said graphic being invisible to the unaided eye;

wherein upon wetting, said hydrolyzable color composition undergoes a hydrolytic reaction resulting in said invisible graphic becoming visible to the unaided eve.

Appl. No. 10/827,088 Docket No. 9606

Reply dated September 10, 2009

Reply to Office Action mailed on June 11, 2009

Customer No. 27752

 (Previously Presented) The article of claim 1 wherein the backsheet is either breathable or non-breathable.

 (Previously Presented) The article of claim 2 wherein the fluid dyestuff is selected from the group consisting of D&C Red 27, D&C Orange 5 and combinations thereof

- 14. (Previously Presented) A disposable absorbent article comprising:
  - a) a liquid pervious topsheet;
  - b) a liquid impervious backsheet that is at least partially joined to the topsheet:
  - an absorbent core disposed at least partially between the topsheet and the backsheet; and
  - d) a wetness indicator printed onto a surface of said backsheet; the wetness indicator comprising a graphic that further comprises at least one hydrolyzable color composition; a first varnish coating disposed over said hydrolyzable color composition; and a second varnish coating disposed beneath said hydrolyzable color composition; said graphic being invisible to the unaided eye;

wherein upon wetting, said hydrolyzable color composition undergoes a hydrolytic reaction forming a carboxylic acid, resulting in said invisible graphic becoming visible to the unaided eye.

- (Previously Presented) The article of claim 14 wherein the backsheet is either breathable or non-breathable.
- (Previously Presented) The article of claim 1 wherein said chemical reaction forms a carboxylic acid.